

# Wall mounted unit

FTXTM-M / RXTM-N



perfera



Guaranteed operation down to -25°C



Practically inaudible



Fireplace logic



2 area intelligent eye



Online controller via app

## Attractive, wall mounted design with perfect indoor air quality

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › Seasonal efficiency values up to A+++ in cooling and heating
- › When installed close to a heating device (e.g. fire place or oven) and the set temperature is reached, the fan keeps on running to have an even temperature throughout the whole house.

- › Cleaner air thanks to Daikin's Flash Streamer technology: you can breathe deep with no worries about impure air
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption

# FTXTM-M + RXTM-N



Indoor unit		FTXTM	30M	40M
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth mm	294x811x272	300x1,040x295
Sound power level	Cooling	dB(A)	60	
	Heating	dB(A)	61	
Sound pressure level	Cooling	High/Medium/Low/Silent operation	45/33 (1)/25/21	46/32 (1)/24/20
	Heating	High/Medium/Low/Silent operation	45/31/22/19	46/31/22/19
Control systems	Infrared remote control		ARC466A55	
	Wired remote control		BRC944B2 / BRC073A1	

(1) See separate drawing for electrical data


Efficiency data		FTXTM + RXTM	30M + 30N	40M + 40N
Cooling capacity	Min./Nom./Max.	kW	0.70/3.00/4.50	0.70/4.00/5.10
Heating capacity	Min./Nom./Max.	kW	0.80/3.20/6.70	0.80/4.00/7.20
Power input	Cooling	Nom.	0.74	1.09
	Heating	Nom.	0.61	0.78
Space cooling	Capacity	Pdesign	3.00	4.00
	Energy efficiency class		A++	
	SEER		7.60	7.70
Space heating (Average climate)	Capacity	Pdesign	3.00	3.80
	Energy efficiency class		A+++	
	SCOPnet/A		5.13	5.31
Nominal efficiency	EER		4.10	3.71
	COP		5.34	5.37

Cooling: T2: indoor temp. 26,6°CDB, 19,4°CWB, outdoor temp. 48°CDB [Btu/hr/W] | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.

Outdoor unit		RXTM	30N	40N
Dimensions	Unit	HeightxWidthxDepth mm	551x763x312	
Sound power level	Cooling	dB(A)	61	
	Heating	dB(A)	61	
Sound pressure level	Cooling	Nom.	48	
	Heating	Nom.	49	
Operation range	Cooling	Ambient	Min.-Max.	°CDB
	Heating	Ambient	Min.-Max.	°CWB
Refrigerant	Type/Charge/GWP	kg/TCO <sub>2</sub> eq	R-32/1.1/-/675	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN19-055

08/18



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.