

Wall mounted unit

ATXP-L + ARXP-L



Siesta



Energy saving during standby mode



Online controller via app



Multi model application

Discreet Siesta wall mounted unit providing high efficiency and comfort

- › Whisper quiet
- › Online controller (optional)
- › Ideal for above door installation
- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

ATXP-L + ARXP-L




Efficiency data		ATXP + ARXP	20L + 20L	25L + 25L	35L + 35L	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	
Power input	Cooling	Min./Nom./Max.	0.31/0.50/0.72	0.31/0.66/0.72	0.29/1.01/1.30	
	Heating	Min./Nom./Max.	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	
Space cooling	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.00	2.50	3.50
	SEER			6.77	6.85	6.56
	Annual energy consumption		kWh/a	104	128	187
Space heating (Average climate)	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.20	2.40	2.80
	SCOP/A			4.64	4.60	4.62
	Annual energy consumption		kWh/a	663	730	847
Nominal efficiency	EER		3.98	3.79	3.45	
	COP		4.77	4.36	4.02	
	Energy labeling Directive	Cooling/Heating	A/A			

Indoor unit		ATXP	20L	25L	35L
Dimensions	Unit HeightxWidthxDepth	mm	286x770x225		
Weight	Unit	kg	9.00		
Air filter	Type	Removable / washable			
Fan	Air flow rate	Cooling	4.4/5.9/7.9 / 9.8	4.4/6.1/8.1 / 10.1	4.5/6.3/8.3 / 11.5
		Heating	5.3/6.5/8.4 / 10.3	5.3/6.7/8.6 / 10.3	5.3/7.0/9.0 / 11.5
Sound power level	Cooling	dBA	55		58
	Heating	dBA	55		58
Sound pressure level	Cooling	Silent operation/Low/High	20/25/39	20/26/40	20/27/43
	Heating	Silent operation/Low/High	21/28/39	21/28/40	21/29/40
Control systems	Infrared remote control		ARC480A11		
	Wired remote control		BRC944B2 / BRC073A1		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

Outdoor unit		ARXP	20L	25L	35L	
Dimensions	Unit HeightxWidthxDepth	mm	550x658x275			
Weight	Unit	kg	28			
Sound power level	Cooling	dBA	60		62	
	Heating	dBA	61		62	
Sound pressure level	Cooling	High	46	48		
	Heating	High	47	48		
Operation range	Cooling	Ambient Min.~Max.	°CDB -10~-46			
	Heating	Ambient Min.~Max.	°CWB -15~-18			
Refrigerant	Type		R-32			
	GWP		675.0			
	Charge		kg/TCO2Eq	0.70/0.48		
Piping connections	Liquid	OD	mm 6,35			
	Gas	OD	mm 9,5			
	Piping length	OU - IU Max.	m 15			
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)		
	Level difference		IU - OU Max.	m 12		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			
Current - 50Hz	Maximum fuse amps (MFA)	A	-			

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN18-047 01/2018



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.