

Floor standing unit

FVXM-F



BLUEEVOLUTION



Online controller
via app



Multi model appli-
cation

Floor standing unit for optimal heating comfort thanks to dual airflow

- › Seasonal efficiency values up to A++ in cooling
- › Its low height (620 mm) enables the unit to fit perfectly beneath a window
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Quiet operation: down to 23dBA sound pressure level
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency

FVXM-F + RXM-M9



Indoor unit		FVXM	25F	35F	50F	
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	600x700x210			
Sound power level	Cooling	dB(A)	52		57	
	Heating	dB(A)	52		58	
Sound pressure level	Cooling	High/Low/Silent operation	dB(A)	38/27/23	39/27/24	44/36/32
	Heating	High/Low/Silent operation	dB(A)	38/26/23	39/27/24	45/36/32
Control systems	Infrared remote control		ARC452A1			


Efficiency data		FVXM + RXM	25F + 25M9	35F + 35M9	50F + 50M9	
Cooling capacity	Nom.	kW	2.50	3.50	5.00	
Heating capacity	Nom.	kW	3.40	4.50	5.80	
Power input	Cooling	Nom.	kW	0.60	1.09	1.55
	Heating	Nom.	kW	0.77	1.19	1.60
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A++			
		Pdesign	kW	2.50	3.50	5.00
		SEER		7.20	6.43	6.80
	Heating (Average climate)	Annual energy consumption	kWh	120	190	257
		Energy efficiency class	A+			
		Pdesign	kW	2.40	2.90	4.20
Nominal efficiency	EER	SCOP/A	4.56	4.00	4.00	
		Annual energy consumption	kWh	737	1,015	1,471
	COP		4.20	3.21	3.23	
			4.42	3.78	3.63	
Energy labeling Directive	Cooling		298	545	773	
	Heating			A	A	

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.

Outdoor unit		RXM	25M9	35M9	50M9	
Dimensions	Unit	HeightxWidthxDepth	550x765x285		735x825x300	
Sound power level	Cooling	dB(A)	59	61	62	
	Heating	dB(A)	59	61	62	
Sound pressure level	Cooling	Nom.	dB(A)	46	49	48
	Heating	Nom.	dB(A)	47	49	49
Operation range	Cooling	Ambient	Min.~Max.	°CDB		
Refrigerant	Type/Charge/GWP	kg/TCO _{eq}	R-32/0.76/0.52/675.0		R-32/1.40/0.95/675	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN18-049

09/17



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.